
Comment


org 8-24-18 rev 8-16-18 cosmo


9-8-21 counters read= after a long power outage, several weeks, fantmrsw 0, fanswon 0, exfanhrs 656hr 18 min, exfancnt 19527, sdrcnt 996, ndrcnt 18787, sremcnt 0, nremcnt 35099.....did not reset any to zero, left alone, also added MOV, and slowed flash on backup light on Smart and here in program 5-19-22 nremont 43868, sremont 0, ndr ont 23458, sdr ont 1522, exfancht 24642, exfanhrs 827h 58m, fansw on 0, fn tmrsw 0, new F type Smart relay installed, redwnld all counts to zero, city IP address installed, FS-05 verified, MOV verified, slo flash verified,


Creator:	AM rev jbl		Project:	Station 25 doors	Customer:	Denver Fire Department
Checked:	5-19-22		Installation:	Door Project	Diagram No.:	3
Date:	2/18/16 7:10 AM/6/10/22 9:12 AM		File:	Sta 25 drs 5-19-22.lsc	Page:	1 / 18


Module A	Address					
IP Addres Subnet M Default ga	ask: 10.126.165.21 ask: 255.255.255.240 ateway 10.126.165.17					
tor:	AM rev jbl		Project:	Station 25 doors	Customer:	Denver Fire Department
ked:	5-19-22	Denver Fire Lineshop	Installation:	Door Project	Diagram No.:	3
	2/18/16 7:10 AM/6/10/22 9:12 AM		File:	Sta 25 drs 5-19-22.lsc	Page:	2 / 18











Sta 25

Creator:

Date:

Checked:

AM rev jbl

2/18/16 7:10 AM/6/10/22 9:12 AM

5-19-22

	Project:	Station 25 doors	Customer:	Denver Fire Department
Denver Fire Lineshop	Installation:	Door Project	Diagram No.:	3


Page:

8 / 18

Sta 25 drs 5-19-22.lsc

File:


PAGE 8




Sta 25

PAGE	9
------	---

Creator:	AM rev jbl	Denver Fire Lineshop	Project:	Station 25 doors	Customer:	Denver Fire Department
Checked:	5-19-22		Installation:	Door Project	Diagram No.:	3
Date:	2/18/16 7:10 AM/6/10/22 9:12 AM		File:	Sta 25 drs 5-19-22.lsc	Page:	10 / 18





B001 buffer(On-delay) : B002 buffer(On-delay) : B009 Nits tmr(Edge-triggered interval time-delay relay) : B010 Sits tmr(Edge-triggered interval time-delay relay) : B011 On-delay) : B011 (On-delay) : B012 It pulse(Asynchronous pulse generator) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : B021(On-delay) : B021(On-delay) : B021(On-delay) :	Rem = off Rem = off 01:00s+ Rem = off 03:00m+ 01:00s Rem = off 02:00m+ 00:50s+ Rem = off 00:50s+ Rem = off 00:50s+ Rem = off 00:50s+ Rem = off 00:00s Rem = off 00:00s 1 Rem = off 00:00s 1 Rem = off 00:00s 1 Rem = off 00:00s Rem = off 00:00s Rem = off 00:00s Rem = off 00:00s Rem = off 00:00s+ 00:00s+ 0:00s+
B009 Nlts tmr(Edge-triggered interval time-delay relay) : B010 Slts tmr(Edge-triggered interval time-delay relay) : B011(On-delay) : B012 It pulse(Asynchronous pulse generator) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) :	Rem = off 03:00m+ 00:00s Rem = off 00:00s+ 00:50s+ Rem = off 00:50s+ Rem = off 00:00s Rem = off 00:00s+ 01:00s Rem = off 02:00m+ 00:00s 1 Rem = off 00:00s+ 1 Rem = off 00:00s+ 1
B010 Slts tmr(Edge-triggered interval time-delay relay) : B011(On-delay) : B012 It pulse(Asynchronous pulse generator) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) :	1 Rem = off 00:00s 1 Rem = off 00:50s+ Rem = off 02:00m+ 01:00s Rem = off 02:00m+ 02:00m+ 02:00m+ 02:00m+ 02:00m+ 02:00m+ 02:00m+ 02:00m+ 02:00m+ 01 Rem = off 15:00s+ Rem = off 02:00m+ 00:00s
B011(On-delay) : B012 It pulse(Asynchronous pulse generator) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B016 Sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) :	1 Rem = off 00:50s+ 01:00s Rem = off 02:00m+ 00:00s 1 Rem = off 15:00m+ 02:00m+ 02:00m+ 02:00m+ 1 Rem = off 15:00s+
B012 It pulse(Asynchronous pulse generator) : B015 Nfn tmr(Edge-triggered interval time-delay relay) : B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) :	Rem = off 05:00s+ 01:00s Rem = off 02:00m+ 00:00s 1 Rem = off 02:00m+ 00:00s 1 Rem = off 02:00m+ 00:00s 1 Rem = off 00:00s 1
B015 Nfn tmr(Edge-triggered interval time-delay relay) : NORTH DOOR RIG EXHAUST FAN TIMER B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : SOUTH DOOR RIG EXHAUST FAN TIMER	Rem = off 02:00m+ 01:00s Rem = off 15:00m+ Rem = off 02:00m+ 00:00s 1 Rem = off 15:00s+
B016 sw tmr (Off-delay) : B017 Sfn tmr(Edge-triggered interval time-delay relay) : SOUTH DOOR RIG EXHAUST FAN TIMER	1 Rem = off 15:00m+ Rem = off 02:00m+ 00:00s 1 Rem = off 15:00s+
B017 Sfn tmr(Edge-triggered interval time-delay relay) : SOUTH DOOR RIG EXHAUST FAN TIMER	Rem = off 02:00m+ 00:00s 1 Rem = off 15:00s+
	1 Rem = off 15:00s+
B021(On-delay) :	
	Dom - off
B024(Edge-triggered interval time-delay relay) : This keeps engineer from repeat remote pushiing	Rem = off 01:50s+ 00:00s 1
B025(Edge-triggered interval time-delay relay) : This keeps engineer from repeat remote pushing	Rem = off 01:50s+ 00:00s 1
B026(On-delay) : NORTH door	Rem = off 07:00s+
B027(Edge-triggered interval time-delay relay) :	Rem = off 14:98s+ 00:00s 1
B029(Edge-triggered interval time-delay relay) : this device starts timer counting from zero with vocalarm	Rem = off 03:34m+ 00:00s 1
B031(Edge-triggered interval time-delay relay) : these devices send a pulse to stop the counting when door is fully closed	Rem = off 00:10s+ 00:00s 1
B032(Edge-triggered interval time-delay relay) :	Rem = off 00:10s+ 0:00s 1
B033(Edge-triggered interval time-delay relay) : this device sends a quick pulse to reset timer	Rem = off 00:10s+ 0:00s 1
B034(On-delay) : SOUTH door	Rem = off 07:00s+
B035(Edge-triggered interval time-delay relay) :	Rem = off 02:00m+ 00:00s 1
	ors Customer: Denver Fire Department
r: AM rev jbl Project: Station 25 doo ed: 5-19-22 Denver Fire Lineshop Installation: Door Project 2/18/16 7:10 AM/6/10/22 9:12 AM File: Sta 25 drs 5-19	Diagram No.: 3

Block Number (Type)	Parameter
B036 nremcnt(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B037(Asynchronous pulse generator) :	Rem = off 03:00s+ 01:00s
B039 sremcnt(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B044 bckupNlt(Edge-triggered interval time-delay relay) :	Rem = off 02:00m+ 00:00s 1
B046 bckupSlt(Edge-triggered interval time-delay relay) :	Rem = off 02:00m+ 00:00s 1
B047(On-delay) :	Rem = off 15:00s+
B048(Edge-triggered interval time-delay relay) :	Rem = off 14:98s+ 00:00s 1
B049(Asynchronous pulse generator) :	Rem = off 03:00s+ 01:00s
B052 ndr cnt(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B055 sdr cnt(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B056 Ndr msg(Message texts) :	Prio = 0 Quit = off Text1: enabled Text2: disabled - CBC - Line1: N - Line2: N - Line3: N - Line4: N - Line5: N - Line6: N Message Destination - Both
B058(Asynchronous pulse generator) :	Rem = off 00:50s+ 00:50s
B059(Edge-triggered interval time-delay relay) :	Rem = off 05:00s+ 00:00s 1
B060(On-delay) :	Rem = off 05:00s+
tor: AM rev jbl Project: Station 25 sked: 5-19-22 Denver Fire Lineshop Installation: Door Proj. : 2/18/16 7:10 AM/6/10/22 9:12 AM File: Sta 25 drs	

Block Number (Type)	Parameter
B061(Edge-triggered interval time-delay relay) :	Rem = off 15:00s+ 00:00s 1
B062 Npulse(Edge-triggered interval time-delay relay) :	Rem = off 00:50s+ 00:00s 1
B063 Spulse(Edge-triggered interval time-delay relay) :	Rem = off 00:50s+ 00:00s 1
B066 Sdr msg(Message texts) :	Prio = 2 Quit = off Lext1: enabled Text2: disabled
S O U T H D O O R I S O P E N Image: Constraint of the state of the	> Ticker setting - CBC - Line1: N - Line2: N - Line4: N - Line6: N - Line6: N Message Destination - Both
Line3.7 B010 Slts tmr-THRest Line4.7 B017 Sfn tmr-THRest	I.
B067(Edge-triggered interval time-delay relay) :	Rem = off 02:00m+ 00:00s 1
B069(Edge-triggered interval time-delay relay) :	Rem = off 02:00m+ 00:00s 1
B070 exfancnt(Up/Down counter) : Rig fan "ON" count	Rem = on On=0+ Off=0 Start=0
B071 exfanhrs(Operating hours counter) : Rig fan hours	MI= 0h 0m+ OT= 0h 0m Q->0=R+En
B072 fansw on(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B073 fn tmrsw(Up/Down counter) :	Rem = on On=0+ Off=0 Start=0
B074(Edge-triggered interval time-delay relay) :	Rem = off 10:00s+ 00:00s 1
B075(Edge-triggered interval time-delay relay) :	Rem = off 10:00s+ 00:00s 1
	25 doors Customer: Denver Fire Department
ked: 5-19-22 Denver Fire Lineshop Installation: Door Pro 2/18/16 7:10 AM/6/10/22 9:12 AM File: Sta 25 or	oject Diagram No.: 3 drs 5-19-22.lsc Page: 15 / 18

B076(Message texts) : Prio = 3 Out = off Text2 disabled R I G E X F A N " O N "	
R I G E X F A N "O N " > Ticker setting - CBC - Line1: N - Line2: N	
B077(Message texts) : R I G F A N T I M E D W I T H S E L E C T O R S W I T C H D B016 sw tmr S W I T C H D B016 sw tmr S W I T C H D B016 sw tmr S W I T C H D B016 sw tmr S W I T C H D B016 sw tmr	
Line3.7 B016 sw tmr -TRest I1(Input) : I1-NORTH DOOR	
I2(Input) : I2-SOUTH DOOR	
I4(Input) : ex fan selector sw on	
I5(Input) : Ex fan selector sw timed	
l6(Input) : I6-VOCALARM	
I10(Input) : I10-NORTH door, receiver	
I11(Input) · I11-SOUTH door, receiver	
Q1(Output) : Q1-APPARATUS BAY LIGHTS	
Q2(Output) : Q2-Rig ex fan	
Q3(Output) : Q3-Backup LED lights	
Creator: AM rev jbl Project: Station 25 doors Customer: Denver Fire	Department
Checked: 5-19-22 Denver Fire Lineshop Installation: Door Project Diagram No.: 3 Date: 2/18/16 7:10 AM/6/10/22 9:12 AM File: Sta 25 drs 5-19-22.lsc Page: 16 / 18	

Block Number (Type)	Parameter
Q4(Output): time: input start counting, needs held to keep counting	
Q5(Output) : timer reset to zero	
Q6(Output) : To NORTH opener, white and orange wires	
Q8(Output) : To south door operator, orange and white wires	

Creator:	AM rev jbl		Project:	Station 25 doors	Customer:	Denver Fire Department
Checked:	5-19-22		Installation:	Door Project	Diagram No.:	3
Date:	2/18/16 7:10 AM/6/10/22 9:12 AM		File:	Sta 25 drs 5-19-22.lsc	Page:	17 / 18

Connection		Label					
l1							
12							
14							
15							
16							
110							
111							
M1							
M2							
M3							
M4							
M5							
M6							
M7							
M9							
M10							
M11							
M12							
M13							
M14							
Q1							
Q2							
Q3							
Q4							
Q5							
Q6							
Q8							
Creator:	AM rev	r jbl		Project:	Station 25 doors	Customer:	Denver Fire Department
Checked: Date:	5-19-2	2 5 7:10 AM/6/10/22 9:12 AM	Denver Fire Lineshop	Installation: File:	Door Project Sta 25 drs 5-19-22.lsc	Diagram No.: Page:	3 18 / 18